

E-Disk[®] Altima[™]

2.5" PATA SSD

E-Disk[®] Altima[™] SSDs set the standard for rugged and reliable data storage in extreme environments.



BitMICRO[®] follows a rigorous testing procedure to deliver the highest quality, military-grade products. E-Disk Altima SSDs are tested to withstand extreme temperatures, shock, vibration, humidity, and altitudes.

Powered by the BitMICRO EDSA[™] flash I/O controller and LUNETATA[™] memory flash interface ASICs, E-Disk Altima SSDs boost system performance by eliminating seek time and latency for faster I/O and sustained transfer rates.

Applications

E-Disk Altima SSDs are ideal for military and industrial applications such as:

- Intelligence, Surveillance & Reconnaissance (ISR)
- Aviation & Avionics
- Industrial & Embedded
- Pipeline Inspection
- Medical Equipment
- Industrial Automation

Features

- Superior Ruggedness
- PowerGuard[®] Data Loss Protection
- SecurErase[®] Power Loss Erase
- SecurErase[®] Mobile Erase
- Low Voltage Detection
- SecurErase[®] Military Sanitization

Copyright © 2017 BitMICRO Networks, Inc. All rights reserved. BitMICRO[®], E-Disk[®], Altima[™], EDSA[™], LUNETATA[™], SecurErase[®], and PowerGuard[®] are trademarks or registered trademarks of BitMICRO Networks, Inc. All other trademarks are the property of their respective owners. Product specifications are subject to change without prior notice. One GB equals 1,073,741,824 bytes when referring to solid state drive capacity. U.S. Patent No. 5,822,251; 5,956,743; 6,529,416; 6,970,890; 6,000,006; 6,317,330; 6,496,939; 6,744,635; 6,757,845; 7,506,098; 7,826,243; 8,010,740; 8,447,908; 8,560,804; 8,093,103; 8,665,601; 8,788,725; 9,099,187; 9,372,755; 9,484,103; 9,552,848. Other patents pending. For additional patent information, please visit www.bitmicro.com/company/research-and-development.

Product Specifications

Physical

Form Factor	2.5"
Mounting	HDD standard, all orientations
Connector	44-Pin 2.00 mm IDE/ATA ANSI
Dimensions (L x W x H)	3.955" x 2.75" x 0.374"
Weight	3.016 oz. to 9.065 oz.

Note: Size and weight numbers are approximate.

Capacity

SLC	20 GB to 300 GB
-----	-----------------

Note: Usable capacity.

Performance

Burst Rate	133 MB/s
------------	----------

Power

Voltage	5V DC (±5%)
---------	-------------

Reliability

Error Correction	Corrects 9 bits per 528 B
Write Endurance	6.74 years @ 100 GB/day write/erase cycles (20 GB drive)

Environmental

Operational Temperature	Commercial: 0 to 70 °C Industrial: -40 to 85 °C
Maximum Temperature Change Rate	3 °C/min
Altitude	-1,200 to 120,000 ft
Humidity	5 to 95% (non-condensing)
Shock	1,500 G
Vibration	16.4G rms

Security

SecurErase Standard Compliance	NISPOM DoD 5220.22-M NSA 130-2 Air Force AFSSI 5020 Army 380-19 IRIG-106 NISPOMSUP AFSSI 5020/2003 AFSSI 5020/2003 CLR NSA 9-12
--------------------------------	---

Warranty

Standard	1 year
Extended (Optional)	Up to 5 years

For more Information

Email: sales@bitmicro.com

Call: +1 (888) 72-FLASH